



February 26, 2007

Mr. Ewald Schmon
R&D Manger
SATA GmbH & Co. KG
Domertalstrasse 20
70806 Kornwesteim
Germany

RE: Rule 2.26 Transfer Efficiency Conditional Approval of the SATA Jet 3000 RP Spray Gun

Dear Mr. Schmon:

The Yolo-Solano Air Quality Management District (District) has performed a compliance review of your product with the requirements of District Rule 2.26 - Motor Vehicle And Mobile Equipment Coating Operations and has examined the written approval you included with your correspondence which contained conditional written approval from the U.S. Environmental Protection Agency Region IX (EPA) and the Indiana Department of Environmental Management.

Rule 2.26, Section 302.3 requires any alternate coating application method demonstrate a transfer efficiency of 65% or greater, and be approved by the EPA.

Based on our review of the submitted correspondence and associated certificates the District agrees that the SATAjet 3000 RP spray guns are capable of achieving a transfer efficiency of 65% or greater and are approved by EPA.

The District grants conditional approval of the SATAjet 3000 RP spray guns for use on any Group I or II vehicle or mobile equipment or their parts or components. This approval is subject to the same conditions outlined in the submitted EPA approval letter dated November 15, 2006 and are repeated below for information:

1. SATA GmbH & Co. KG shall supply written notification with each SATAjet 3000 RP spray guns sold or distributed for use within the jurisdiction of the District that the spray gun is only approved for the application of coatings subject to Rule 2.26.
2. This approval is only valid if the air pressure supplied to the SATAjet 3000 RP spray guns is equal to or less than 35 psig. SATA GmbH & Co. KG shall supply

February 26, 2007

Mr. Schmon


Page 2

written notification with each SATAjet 3000 RP spray gun sold or distributed for use within the District that the maximum air pressure supplied to the spray gun shall not exceed 35 psig.

3. SATA GmbH & Co. KG shall supply a SATA air micrometer with gauge with each SATAjet 3000 RP spray gun sold or distributed for use within the jurisdiction of the District. SATA GmbH & CO. KG shall supply written notification with each SATAjet 3000 RP spray gun sold or distributed within the District that the SATA air micrometer with gauge shall be attached to the spray gun and be in good working condition whenever the spray gun is in operation.
4. This approval is only valid if during actual operation the SATAjet 3000 RP spray gun is equipped with properly operating SATA air micrometer and gauge.
5. SATA GmbH & Co. KG shall add a clearly visible permanent label specifying the that the inlet air pressure shall not exceed 35 psig to all SATAjet 3000 RP spray guns sold or distributed for use within the District.
6. This approval is only valid if during actual operation the SATAjet 3000 RP spray guns are labeled as described in condition 5.
7. This approval is only valid for the SATAjet 3000 RP spray gun models tested.

If you have any questions please contact me at (530) 757-3667.

Sincerely,



Susan K. McLaughlin
Supervising Air Quality Engineer