

43301 Division St., Suite 206
Lancaster CA 93535

(661) 723-8070
Fax (661) 723-3450

Charles L. Fryxell, Air Pollution Control Officer

In reply, please refer to AV0104/005

January 14, 2004

SATA Farbspritztechnik GmbH & Co. KG
Domertalstraße 20
70806 Kornwestheim, Germany
Attn: Ewald Schmon

VIA FAX

Re: Rule 1151 Transfer Efficiency Approval of the SATAjetRP Spray Gun.

Dear Mr. Schmon:

The Antelope Valley Air Quality Management District (AVAQMD) received your letter dated December 18, 2003 requesting approval to offer and sell SATA spray guns within the jurisdiction of the AVAQMD.

The AVAQMD approves the use of the SATAjetRP and SATAjet RP Digital 2 spray guns for operations subject to Rule 1151, *Motor Vehicle and Mobile Equipment Non-Assembly Line Coating Operations*.

The approval is subject to the following conditions that are also required by the South Coast Air Quality Management District.


1. SATA Farbspritztechnik GmbH & Co. KG shall supply written notification with each paint spray gun sold that the spray gun is only approved for the application of coatings subject to Rule 1151.
2. Approval is only valid if the air pressure supplied to the SATAjet RP and the SATAjet RP Digital 2 paint spray guns is equal or less than 35 psig.
3. SATA Farbspritztechnik GmbH & Co. KG shall supply a Sata air micrometer with gauge 0/845 (Product Number 27771) modified to clearly identify the maximum allowable spray gun inlet air pressure with each SATAjet RP spray gun sold for use in the AVAQMD. The required modification shall provide a visual confirmation that the maximum allowed air pressure is 35 psig such as color coding that gauge to make the area of the gauge at and below 35 psig green and the above 35 psig red or other design approved by the AVAQMD.

SATA Farbspritztechnik GmbH & Co. KG shall supply written notification with each SATAjet RP spray gun sold or distributed for use in the AVAMD that the Sata air micrometer with gauge 0/845 (product number 27771) modified as described above shall be attached to the spray gun and be in good working condition whenever the spray gun is in operation.

4. SATA Farbspritztechnik GmbH & Co. KG shall add a clearly visible permanent label specifying that the inlet pressure shall not exceed 35 psig to all SATAjet RP Digital 2 spray guns sold or distributed for use in the Antelope Valley Air Quality Management District.
5. This approval is only valid for the SATAjet RP and SATAjet RP Digital 2 spray gun models.

If you have any questions regarding this approval please call me at (661) 723-8070.

Sincerely,



Bret S. Banks
Operations Manager